



SEE PLAN VIEW FOR
MANWAY ORIENTATION

VESSEL STANDARDS

VESEL MATERIALS : CARBON STEEL	LIQUID DRAIN ASSEMBLY : 1" DRAIN W/ PLUG
LINING : HIGH SOLIDS EPOXY	VOLUME OF VESSEL : 400 FT ³
EXTERIOR PAINT : ACRYLIC ALKYD ENAMEL	STANDARD/MAX CARBON FILL : 4400 LBS / 7400 LBS
HEAD THICKNESS : 3/16"	SHIP WT. OPERATING WT.STD.FILL : 7515 LBS / 10815 LBS
BOTTOM PLATE THICKNESS : 3/16"	CARBON TYPE : TIGG 5CP4MM VAPOR PHASE
INTERNALS : PLENUM	MAX. OPERATING PRESSURE : 15 PSIG
ADSORBENT OUTLET ASSEMBLY : 18" MANWAY	MAX. OPERATING TEMP. : 180°F

NO.	REVISION	BY	DATE
PROJECT			
PROJ. NO.		SALES	
P.O. NO.			
<small>THIS DRAWING AND DESIGN ARE THE PROPERTY OF TIGG CORP. AND SHALL NOT BE REPRODUCED IN WHOLE OR IN PART, NOR EMPLOYED FOR ANY PURPOSE OTHER THAN SPECIFICALLY PERMITTED IN WRITING BY TIGG CORP. THIS DRAWING LOANED SUBJECT TO RETURN ON DEMAND.</small>			
DRAWN BY	JB		
DESIGN BY	BB		
CHKD. BY	BB		
DATE	2/23/05		
SCALE	NTS		
DWG. NO.		REV.	
N-5000-PDB-1001		0	



N-5000-PDB