


5	HINGED MANWAY	JB	9/6/06
4	REVISE CARBON FILL	JB	1/20/04
3	SUBTRACT VENT	JB	5/14/03
2	CHANGE EXTERIOR PAINT	JB	5/7/03
1	TITLE BLOCK	JB	8/27/02
NO.	REVISION	BY	DATE

PROJECT		
PROJ. NO.	SALES	
P.O. NO.		
<small>THIS DRAWING AND DESIGN ARE THE PROPERTY OF TIGG CORP. AND SHALL NOT BE REPRODUCED IN WHOLE OR IN PART, NOR EMPLOYED FOR ANY PURPOSE OTHER THAN SPECIFICALLY PERMITTED IN WRITING BY TIGG CORP. THIS DRAWING LOANED SUBJECT TO RETURN ON DEMAND.</small>		
DRAWN BY	ZS	
DESIGN BY	BL	
CHKD. BY	BL	
DATE	9/6/06	DWG. NO.
SCALE	NTS	REV.

VESSEL STANDARDS

VESSEL MATERIALS : A36 CARBON STEEL	LIQUID DRAIN ASSEMBLY : 1" HDPE PLUG
LINING : HIGH SOLIDS EPOXY	VOLUME OF VESSEL : 82 FT (NOT INCLUDING TOP HEAD)
EXTERIOR PAINT : ACRYLIC ALKYD ENAMEL	STANDARD/MAX CARBON FILL : 1500 LBS / 2000 LBS
HEAD THICKNESS : 3/16"	SHIP WT. STD.FILL : 2925 LBS
BOTTOM PLATE THICKNESS : 3/16"	CARBON TYPE : TIGG 4MM PELLET VAPOR PHASE
INTERNALS : PLENUM	MAX. OPERATING PRESSURE : 15 PSIG
ADSORBENT OUTLET ASSEMBLY : 20" MANWAY	MAX. OPERATING TEMP. : 180°F

N-1800-PDB

N-1800PDN-1001

5