



VESSEL STANDARDS

VESSEL MATERIALS : CARBON STEEL	LIQUID DRAIN ASSEMBLY : PROCESS DISCHARGE
LINING : PLASITE	VOLUME OF VESSEL : 585 FT ³
EXTERIOR PAINT : ACRYLIC ALKYD ENAMEL	MAX. MEDIA FILL : 450 FT ³
HEAD THICKNESS : ASME F&D 5/16"	EMPTY WT. : 5500 LBS
SHELL THICKNESS : SA-36 1/4"	MAX. OPERATING PRESSURE : 50 PSI
INTERNALS : PVC & PPL	MAX. OPERATING TEMP. : 150°F
ADSORBENT OUTLET ASSEMBLY : 4" 150 LB FLANGED NOZZLE	

NO.	REVISION	BY	DATE
PROJECT C-500-T (RENTAL UNIT)			
PROJ. NO.	SALES		
P.O. NO.			
<small>THIS DRAWING AND DESIGN ARE THE PROPERTY OF TIGG CORP. AND SHALL NOT BE REPRODUCED IN WHOLE OR IN PART, NOR EMPLOYED FOR ANY PURPOSE OTHER THAN SPECIFICALLY PERMITTED IN WRITING BY TIGG CORP. THIS DRAWING LOANED SUBJECT TO RETURN ON DEMAND.</small>			
DRAWN BY	JB		
DESIGN BY	BB		
CHKD. BY	BB		
DATE	11/3/05	DWG. NO.	C-500-T-1001
SCALE	NTS	REV.	0



PLAN & ELEVATION