



DESCRIPTION

TIGG LMRA is a high activity coal based activated carbon which is specially impregnated for removal of mercury. The extensive surface area permits optimum distribution of the impregnated reagent for maximum reaction rate and full stoichiometric utilization. The finished activated carbon retains sufficient unimpregnated surface area to function as an effective adsorbent in addition to its primary chemisorption role, thus allowing reduction of a wide variety of organic contaminants.

TYPICAL PROPERTIES

U.S. Sieve, 90 wt% min	12 x 40*
Apparent Density, (dense packing)	
g/cc	0.50 – 0.57
lbs/ft ³	32 – 36
Hardness No. - min	97
Moisture – wt% max (as packaged)	3
Iodine Number, mg/g, min	1000
Mercury capacity, wt %	30

*Also available as 8 x 30 mesh when a lower pressure drop is required.

TYPICAL APPLICATIONS

TIGG LMRA activated carbon is recommended for applications where mercury and other heavy metals, as well as organics, are to be removed from water.

Standard packaging of the activated carbon is in 1000 lb supersaks. Metal drums, fiber drums and 50 lb bags, are available for a premium.

Wet drained activated carbon adsorbs oxygen from the air. Therefore, when workers need to enter a vessel containing wet activated carbon, they should follow confined space/low oxygen level procedures. Activated carbon dust does not present an explosion hazard.

